

Interior Waterborne Eco Paint
PRIMA
zero VOC base & colorant

MAKING AN IMPACT
ON YOUR WALLS NOT
THE ENVIRONMENT

SAFE • GREEN • CLEAN



colours by **DAVID OLIVER**

TECHNICAL DATA SHEET

PRODUCT FEATURES

- Ecologically Responsible
- Zero VOC in Base & Colorants
- Available tinted
- High-Hiding
- Low Odor
- Quick return to service
- Contributes to LEED points
- Manufactured in the USA

LIMITATIONS

- Do not apply when air and surface temperature are below 50°F.

RECOMMENDED FOR RESIDENTIAL USE ON:

- Walls & Ceilings
- Sheetrock
- Plaster
- Masonry
- Wood & Metal

RECOMMENDED FOR ARCHITECTURAL USE IN:

- Hospitals
- Schools
- Assisted Living Facilities

TECHNICAL DATA

FINISH	Flat
VEHICLE TYPE	Co-polymer
PIGMENT TYPE	Titanium Dioxide
SOLVENT TYPE	Water
% SOLID BY WEIGHT	52%
WEIGHT/PER GALLON	11.50 lbs./gal
RECOMMENDED DRY FILM BY COAT	1.5 to 2.5 mils per coat
THEORETICAL COVERAGE	350-450 sq ft./gallon
VISCOSITY @ 77° F	85 KU +/- 5
DRY TIME AVERAGE	To touch: 1 hour. To recoat: 2 hours.
APPLICATION METHOD	Brush, roller or spray
SHELF LIFE	1 year at proper storage conditions
PACKAGED	Quart, gallon and five gallon pails
FLASH POINT	N/A
STORAGE CONDITIONS	50° F to 90° F

Stark Carpet Corp.

979 Third Avenue New York, NY 10022 Phone 212.752.9000 Fax 212.753.3694 www.starkpaint.com

Interior Waterborne Eco Paint PRIMA zero VOC base & colorant

MAKING AN IMPACT
ON YOUR WALLS NOT
THE ENVIRONMENT



colours by **DAVID OLIVER**

TECHNICAL DATA SHEET

COMMITMENT TO OUR ENVIRONMENT

Stark Paint, colours by David Oliver is formulated to be earth-friendly and ecologically responsible. Our paints are water based with little odor and are non-toxic. The collection is environmentally safe to use, easy to transport and there are no VOC's in the base or colorants. When completely dry, Stark Paint, colours by David Oliver is safe for children and pets, protecting our environment and your home for many years to come.

COVERAGE

Depending on porosity and texture of substrate

SURFACE PREPARATION

Surfaces to be painted must be clean, dry, and free of wax, grease, scaling paint and mildew. Glossy areas should be dulled. New plaster and masonry surfaces must be allowed to cure 30 days before applying Prima base coat.

PRIMING

For best results use Stark Paint Prima.

APPLICATION

Use product when surface temperature is above 50°F (10°C). Stir thoroughly before use, apply one or two coats. For best results, use a premium applicator for latex paints. This product can be applied by brush, roller or spray.

CLEAN UP

Use warm water and soap.

FIRST AID

Use only with adequate ventilation. Ensure fresh air entry during application and drying. Do not breathe spray mist or sanding dust. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and prolonged or repeated contact with skin. Close container after each use. Wash thoroughly after handling. In case of eye contact, flush immediately with plenty of water for at least 15 minutes. For skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

WARNING

If you scrape, sand or remove old paint you may release lead dust. Lead dust is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a Niosh approved respirator to control lead exposure. Carefully clean up with a hepa vacuum and a wet mop. Before painting, find out how to protect yourself and your family by contacting the national lead information hotline at 1.800.424.Lead or log on to www.epa.gov/lead. KEEP OUT OF REACH OF CHILDREN. PROTECT FROM FREEZING.

DISCLAIMER

The information provided whether technical advice, verbal or in writing or by way of color chart trials is for guidance and is given in good faith without warranty since skill of application and site conditions are beyond our control. Within batch variation tolerance, colors are correct at the time of production. Color changes according to its surroundings. Slight variations can occur between finishes according to light conditions and sheen levels. We reserve the right to amend any of our colors or finishes at any time. The manufacturer's guarantee is limited to product replacement or value of the original goods purchased. All our paint products are made to order and therefore no goods are supplied on a return basis. All orders are accepted subject to our standard terms and conditions of sale as listed at www.starkpaint.com. This does not affect your statutory rights.

Interior Waterborne Eco Paint
PORCELAIN SHELL
zero VOC base & colorant

MAKING AN IMPACT
ON YOUR WALLS NOT
THE ENVIRONMENT

SAFE • GREEN • CLEAN



colours by **DAVID OLIVER**

TECHNICAL DATA SHEET

PRODUCT FEATURES

- Ecologically Responsible
- Zero VOC in Base & Colorants
- 240 Designer Colors
- Infinite Custom Colors available
- High-Hiding
- Low Odor
- Quick return to service
- Contributes to LEED points
- Manufactured in the USA

LIMITATIONS

- Do not apply when air and surface temperature are below 50°F.

RECOMMENDED FOR RESIDENTIAL USE ON:

- Walls & Ceilings
- Sheetrock
- Plaster
- Masonry
- Primed Wood & Metal

RECOMMENDED FOR ARCHITECTURAL USE IN:

- Hospitals
- Schools
- Assisted Living Facilities

TECHNICAL DATA

FINISH	PASTEL BASE Eggshell
VEHICLE TYPE	Co-polymer
PIGMENT TYPE	Titanium Dioxide
SOLVENT TYPE	Water
% SOLID BY WEIGHT	55%
WEIGHT/PER GALLON	11.50 lbs./gal
RECOMMENDED DRY FILM BY COAT	1.5 to 2.5 mils per coat
THEORETICAL COVERAGE	375-475 sq ft./gallon
VISCOSITY @ 77° F	90 KU +/- 5
DRY TIME AVERAGE	To touch: 1 hour. To recoat: 4 hours. To service: 14 days.
APPLICATION METHOD	Brush, roller or spray
SHELF LIFE	1 year at proper storage conditions
PACKAGED	Quart, gallon and five gallon pails
FLASH POINT	N/A
STORAGE CONDITIONS	50° F to 90° F

Stark Carpet Corp.

979 Third Avenue New York, NY 10022 Phone 212.752.9000 Fax 212.753.3694 www.starkpaint.com

Interior Waterborne Eco Paint
PORCELAIN SHELL
zero VOC base & colorant

MAKING AN IMPACT
ON YOUR WALLS NOT
THE ENVIRONMENT



colours by **DAVID OLIVER**

TECHNICAL DATA SHEET

COMMITMENT TO OUR ENVIRONMENT

Stark Paint, colours by David Oliver is formulated to be earth-friendly and ecologically responsible. Our paints are water based with little odor and are non-toxic. The collection is environmentally safe to use, easy to transport and there are no VOC's in the base or colorants. When completely dry, Stark Paint, colours by David Oliver is safe for children and pets, protecting our environment and your home for many years to come.

COVERAGE

Depending on porosity and texture of substrate

SURFACE PREPARATION

Surfaces to be painted must be clean, dry, and free of wax, grease, scaling paint and mildew. Glossy areas should be dulled. New plaster and masonry surfaces must be allowed to cure 30 days before applying Prima base coat.

PRIMING

For best results use Stark Paint Prima.

APPLICATION

Use product when surface temperature is above 50°F (10°C). Stir thoroughly before use, apply one or two coats. For best results, use a premium applicator for latex paints. This product can be applied by brush, roller or spray.

CLEAN UP

Use warm water and soap.

FIRST AID

Use only with adequate ventilation. Ensure fresh air entry during application and drying. Do not breathe spray mist or sanding dust. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and prolonged or repeated contact with skin. Close container after each use. Wash thoroughly after handling. In case of eye contact, flush immediately with plenty of water for at least 15 minutes. For skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

WARNING

If you scrape, sand or remove old paint you may release lead dust. Lead dust is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a Niosh approved respirator to control lead exposure. Carefully clean up with a hepa vacuum and a wet mop. Before painting, find out how to protect yourself and your family by contacting the national lead information hotline at 1.800.424.Lead or log on to www.epa.gov/lead. KEEP OUT OF REACH OF CHILDREN. PROTECT FROM FREEZING.

DISCLAIMER

The information provided whether technical advice, verbal or in writing or by way of color chart trials is for guidance and is given in good faith without warranty since skill of application and site conditions are beyond our control. Within batch variation tolerance, colors are correct at the time of production. Color changes according to its surroundings. Slight variations can occur between finishes according to light conditions and sheen levels. We reserve the right to amend any of our colors or finishes at any time. The manufacturer's guarantee is limited to product replacement or value of the original goods purchased. All our paint products are made to order and therefore no goods are supplied on a return basis. All orders are accepted subject to our standard terms and conditions of sale as listed at www.starkpaint.com. This does not affect your statutory rights.

Interior Waterborne Eco Paint
LACQUER GLOSS
zero VOC base & colorant

MAKING AN IMPACT
ON YOUR WALLS NOT
THE ENVIRONMENT

SAFE • GREEN • CLEAN



colours by **DAVID OLIVER**

TECHNICAL DATA SHEET

PRODUCT FEATURES

- Ecologically Responsible
- Zero VOC in Base & Colorants
- 240 Designer Colors
- Infinite Custom Colors available
- Custom colors available
- High-Hiding
- Low Odor
- Quick return to service
- Contributes to LEED points
- Manufactured in the USA

LIMITATIONS

- Do not apply when air and surface temperature are below 50°F.

RECOMMENDED FOR RESIDENTIAL USE ON:

- Walls & Ceilings
- Sheetrock
- Plaster
- Masonry
- Primed Wood & Metal

RECOMMENDED FOR ARCHITECTURAL USE IN:

- Hospitals
- Schools
- Assisted Living Facilities

TECHNICAL DATA

FINISH	PASTEL BASE
VEHICLE TYPE	Gloss
PIGMENT TYPE	Co-polymer
SOLVENT TYPE	Titanium Dioxide
% SOLID BY WEIGHT	Water
WEIGHT/PER GALLON	55%
RECOMMENDED DRY FILM BY COAT	11.50 lbs./gal
THEORETICAL COVERAGE	1.5 to 2.5 mils per coat
VISCOSITY @ 77° F	375-475 sq ft./gallon
DRY TIME AVERAGE	90 KU +/- 5
APPLICATION METHOD	To touch: 1 hour. To recoat: 4 hours. To service: 14 days.
SHelf LIFE	Brush, roller or spray
PACKAGED	1 year at proper storage conditions
FLASH POINT	Quart, gallon and five gallon pails
STORAGE CONDITIONS	N/A
	50° F to 90° F

Stark Carpet Corp.

979 Third Avenue New York, NY 10022 Phone 212.752.9000 Fax 212.753.3694 www.starkpaint.com

Interior Waterborne Eco Paint LACQUER GLOSS zero VOC base & colorant

MAKING AN IMPACT
ON YOUR WALLS NOT
THE ENVIRONMENT



colours by **DAVID OLIVER**

TECHNICAL DATA SHEET

COMMITMENT TO OUR ENVIRONMENT

Stark Paint, colours by David Oliver is formulated to be earth-friendly and ecologically responsible. Our paints are water based with little odor and are non-toxic. The collection is environmentally safe to use, easy to transport and there are no VOC's in the base or colorants. When completely dry, Stark Paint, colours by David Oliver is safe for children and pets, protecting our environment and your home for many years to come.

COVERAGE

Depending on porosity and texture of substrate

SURFACE PREPARATION

Surfaces to be painted must be clean, dry, and free of wax, grease, scaling paint and mildew. Glossy areas should be dulled. New plaster and masonry surfaces must be allowed to cure 30 days before applying Prima base coat.

PRIMING

For best results use Stark Paint Prima.

APPLICATION

Use product when surface temperature is above 50°F (10°C). Stir thoroughly before use, apply one or two coats. For best results, use a premium applicator for latex paints. This product can be applied by brush, roller or spray.

CLEAN UP

Use warm water and soap.

FIRST AID

Use only with adequate ventilation. Ensure fresh air entry during application and drying. Do not breathe spray mist or sanding dust. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and prolonged or repeated contact with skin. Close container after each use. Wash thoroughly after handling. In case of eye contact, flush immediately with plenty of water for at least 15 minutes. For skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

WARNING

If you scrape, sand or remove old paint you may release lead dust. Lead dust is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a Niosh approved respirator to control lead exposure. Carefully clean up with a hepa vacuum and a wet mop. Before painting, find out how to protect yourself and your family by contacting the national lead information hotline at 1.800.424.Lead or log on to www.epa.gov/lead. KEEP OUT OF REACH OF CHILDREN. PROTECT FROM FREEZING.

DISCLAIMER

The information provided whether technical advice, verbal or in writing or by way of color chart trials is for guidance and is given in good faith without warranty since skill of application and site conditions are beyond our control. Within batch variation tolerance, colors are correct at the time of production. Color changes according to its surroundings. Slight variations can occur between finishes according to light conditions and sheen levels. We reserve the right to amend any of our colors or finishes at any time. The manufacturer's guarantee is limited to product replacement or value of the original goods purchased. All our paint products are made to order and therefore no goods are supplied on a return basis. All orders are accepted subject to our standard terms and conditions of sale as listed at www.starkpaint.com. This does not affect your statutory rights.

Interior Waterborne Eco Paint
VELVET EMULSION
zero VOC base & colorant

MAKING AN IMPACT
ON YOUR WALLS NOT
THE ENVIRONMENT

SAFE • GREEN • CLEAN



colours by **DAVID OLIVER**

TECHNICAL DATA SHEET

PRODUCT FEATURES

- Ecologically Responsible
- Zero VOC in Base & Colorants
- 240 Designer Colors
- Infinite Custom Colors available
- High-Hiding
- Low Odor
- Quick return to service
- Contributes to LEED points
- Manufactured in the USA

LIMITATIONS

- Do not apply when air and surface temperature are below 50°F.

RECOMMENDED FOR RESIDENTIAL USE ON:

- Walls & Ceilings
- Sheetrock
- Plaster
- Masonry
- Primed Wood & Metal

RECOMMENDED FOR ARCHITECTURAL USE IN:

- Hospitals
- Schools
- Assisted Living Facilities

TECHNICAL DATA

FINISH	PASTEL BASE
VEHICLE TYPE	Flat
PIGMENT TYPE	Co-polymer
SOLVENT TYPE	Titanium Dioxide
% SOLID BY WEIGHT	Water
WEIGHT/PER GALLON	60%
RECOMMENDED DRY FILM BY COAT	12.50 lbs./gal
THEORETICAL COVERAGE	1.5 to 2.5 mils per coat
VISCOSITY @ 77° F	375-475 sq ft./gallon
DRY TIME AVERAGE	95 KU +/- 5
APPLICATION METHOD	To touch: 1 hour. To recoat: 4 hours. To service: 14 days.
SHelf LIFE	Brush, roller or spray
PACKAGED	1 year at proper storage conditions
FLASH POINT	Quart, gallon and five gallon pails
STORAGE CONDITIONS	N/A
	50° F to 90° F

Stark Carpet Corp.

979 Third Avenue New York, NY 10022 Phone 212.752.9000 Fax 212.753.3694 www.starkpaint.com

Interior Waterborne Eco Paint VELVET EMULSION zero VOC base & colorant

MAKING AN IMPACT
ON YOUR WALLS NOT
THE ENVIRONMENT



colours by **DAVID OLIVER**

TECHNICAL DATA SHEET

COMMITMENT TO OUR ENVIRONMENT

Stark Paint, colours by David Oliver is formulated to be earth-friendly and ecologically responsible. Our paints are water based with little odor and are non-toxic. The collection is environmentally safe to use, easy to transport and there are no VOC's in the base or colorants. When completely dry, Stark Paint, colours by David Oliver is safe for children and pets, protecting our environment and your home for many years to come.

COVERAGE

Depending on porosity and texture of substrate

SURFACE PREPARATION

Surfaces to be painted must be clean, dry, and free of wax, grease, scaling paint and mildew. Glossy areas should be dulled. New plaster and masonry surfaces must be allowed to cure 30 days before applying Prima base coat.

PRIMING

For best results use Stark Paint Prima.

APPLICATION

Use product when surface temperature is above 50°F (10°C). Stir thoroughly before use, apply one or two coats. For best results, use a premium applicator for latex paints. This product can be applied by brush, roller or spray.

CLEAN UP

Use warm water and soap.

FIRST AID

Use only with adequate ventilation. Ensure fresh air entry during application and drying. Do not breathe spray mist or sanding dust. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and prolonged or repeated contact with skin. Close container after each use. Wash thoroughly after handling. In case of eye contact, flush immediately with plenty of water for at least 15 minutes. For skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

WARNING

If you scrape, sand or remove old paint you may release lead dust. Lead dust is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a Niosh approved respirator to control lead exposure. Carefully clean up with a hepa vacuum and a wet mop. Before painting, find out how to protect yourself and your family by contacting the national lead information hotline at 1.800.424.Lead or log on to www.epa.gov/lead. KEEP OUT OF REACH OF CHILDREN. PROTECT FROM FREEZING.

DISCLAIMER

The information provided whether technical advice, verbal or in writing or by way of color chart trials is for guidance and is given in good faith without warranty since skill of application and site conditions are beyond our control. Within batch variation tolerance, colors are correct at the time of production. Color changes according to its surroundings. Slight variations can occur between finishes according to light conditions and sheen levels. We reserve the right to amend any of our colors or finishes at any time. The manufacturer's guarantee is limited to product replacement or value of the original goods purchased. All our paint products are made to order and therefore no goods are supplied on a return basis. All orders are accepted subject to our standard terms and conditions of sale as listed at www.starkpaint.com. This does not affect your statutory rights.